

FSM1060

10.4-inch Industrial LCD Monitor

Features

- 10.4" TFT LCD With Resolution 1024 x 768
- 1000nit High Brightness for Sunlight Readable (Optional)
- P-CAP Touch Screen / Resistive Touch Screen (Optional)
- Extra Slim Type, only 20.5mm Thickness



SPECIFICATION

Display	Size/Panel Type	10.4 " TFT LCD Panel
	Resolution	1024 x 768
	Brightness (cd/m ²)	400 cd/m ² (Optional: 1000 cd/m ²)
	Contrast Ratio	3000:1
	Response Time	30ms
	Backlight	LED Backlight Unit
	Colors	16.2M Colors
	Viewing Angle (H/V)	178°/178°
	Surface Hardness	3H, Anti-Glare Coating
Touch Screen	Touch Screen Type	P-CAP Touch / Resistive Touch (Optional)
	Surface Hardness	7H / 3H
Environment	Operating Temperature	0°~+50°C
	Storage Temperature	-20°C~+60°C
	Humidity	5%~90% RH(Non-Condensing)
	Waterproof Rating	IP65 Waterproof Front Bezel
System	OSD	Menu, Auto, On/Off, Up, Down
	I/O Interface	DVI, HDMI, VGA, DC in
	Power Input	DC12V Input, w/ AC100~240V Power Adapter
	Power Consumption	18W
	Certification	FCC/CE/RoHS Compliance
	Mounting	VESA 75 x 75mm; 100 x 100mm
	Dimension/Weight	290.0mm(W) x 240.5mm(H) x 20.5mm(D)/1.4kgs

Specifications subject to change without notice

ORDERING CODE

FSM1060-XXXX

- PCT = P-CAP Touch Screen
- RT = Resistive Touch Screen
- HB1000 = 1000nits High Brightness
- W = Wide Temperature, -30°~+60°C
- LS = Light Sensor, Auto Dimming
- OB = Optical Bonding

ACCESSORIES

- VGA Cable x 1 (1.8M)
- AC/DC Power Adapter 1 (1.8M)

