

F501600

15.6" OPEN FRAME INDUSTRIAL LCD MONITOR

FEATURES

- 15.6" Industrial Grade LCD Panel
- Resolution up to 1920 x 1080
- Mounting Brackets Design for Easy Installation
- 1000nits /1800nits High Brightness for Sunlight Readable (Option)
- Wide Temperature Support -30 to 60°C (Option)



SPECIFICATION

Display	Size / Panel Type	15.6" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness	400 cd/m ² (Option : 1000 / 1800 cd/m ²)
	Contrast Ratio	500 : 1
	Response Time	8 ms
	Backlight	LED Backlight Unit
	Colors	16.2M Colors
	Viewing Angle	170° / 160°
	Surface Hardness	3H, Anti-Glare
Cover Lens	Cover Lens Type	N/A
	Option	Protection Glass / Resistive Touch / PCAP Touch
Environment	Operating Temperature	0°~+50°C
	Storage Temperature	-20°~+60°C
	Humidity	5%~95% RH (Non-Condensing)
System	OSD	Menu , Auto , On/Off , Up , Down
	I/O Interface	VGA x 1, DVI x 1, HDMI x 1, DC in w/ 2pin Terminal Block
	Power Input	12VDC Input w/AC100~240V Power Adapter
	Power Consumption	25W
	Compliance	FCC/CE/RoHS Compliance
	Mounting	4 Side Mounting Brackets ; VESA 100 x 100 mm
Dimension / Weight	367mm (W) x 227.9mm (H) x 35mm (D) / 4kgs	

Specifications subject to change without notice

ACCESSORIES

- VGA Cable x 1
- AC/DC Power Adapter x 1

